P170 SERIES ABS CASE PRESSURE GAUGE

Size : 1"(25mm), 1.5"(40mm), 2"(50mm), 2.5"(63mm)

Measuring Range : compound, vacuum 76cmHg (30"Hg) up to 15,000 psi (1,000 bar)

Dial : white aluminum with markings and graduations

Window : snap-in plastic

Pointer : black finished aluminum

Case : black ABS

Movement : brass Socket : brass

Bourdon Tube : phosphor bronze C-tube for vacuum to 800 psi, spiral tube wound for

1,000psi to 15,000 psi

Connection : 1/8", 1/4", 3/8", 1/2"

Mounting : bottom, center back mount

Accuracy : 1.5",2" ($\pm 2.5\%$ of full scale), 2.5" ($\pm 1.5\%$ of full scale)

Operating Temperature Limit : $-20 \sim 60^{\circ}\text{C} \text{ (} -4 \sim 140^{\circ}\text{F)}$

Application : water, air, gas, pump, compressor, regulator and other working fluid

not in corrosion

P-A (Direct Mount, Bottom Connection)







P-AD (Direct Mount, Center Back Connection)







P170 SERIES ABS CASE PRESSURE GAUGE

P-AD-25 (Direct Mount, Center Back Connection)







