

## P600 SERIES LOW PRESSURE GAUGE

Size	: 2"(50mm), 2.5"(63mm) , 3"(75mm), 4"(100mm)
Measuring Range	: vacuum 4"H <sub>2</sub> O up to 15 psi
Dial	: white aluminum with markings and graduations
Window	: plastic, glass, twist lock polycarbonate
Pointer	: black finished aluminum
Ring	: black painted steel, plating steel
Case	: black painted steel, plating steel
Movement	: brass
Socket	: brass
Diaphragm Capsule	: phosphor bronze
Connection	: 1/8", 1/4", 3/8", 1/2"
Mounting	: bottom and center back with flush mount, U-clamp
Accuracy	: $\pm 3-2-3\%$ of full scale
Operating Temperature Limit	: -20 ~ 60°C ( -4 ~ 140 °F )
Application	: gas burner, suction regulator, vacuum pump, gas leak detector, air compressor, air filter, gas measurement, vacuum oven and respirator, any low pressure pneumatic system

### AQ-A (Direct Mount, Bottom Connection)



### AQ-AD (Direct Mount, Center Back Connection)



## P600 SERIES LOW PRESSURE GAUGE

### AQ-UD (Flush Mount, Center Back with U-clamp)



### AQ-DU (Flush Mount, Lower Back Connection)

