

## P200 SERIES ALL STAINLESS STEEL PRESSURE GAUGE

Size	: 1.5" (40mm), 2" (50mm), 2.5" (63mm), 3" (75mm), 4" (100mm), 6" (150mm)
Measuring Range	: compound, vacuum 76cmHg (30"Hg) up to 15,000 psi ( 1,000 bar )
Dial	: white aluminum with markings and graduations
Window	: polycarbonate, glass
Pointer	: black finished aluminum
Ring	: 304 stainless steel
Case	: 304 stainless steel
Filling	: dry and fill-able (oil type available glycerin, silicone)
Movement	: 304 stainless steel
Socket	: 316 stainless steel
Bourdon Tube	: 316L C-tube for vacuum to 1,000 psi, spiral tube wound for 1,000 psi to 15,000 psi
Connection	: 1/8", 1/4", 3/8", 1/2"
Mounting	: bottom and center back with surface, flush mount and U-clamp
Accuracy	: 1.5", 2" ( $\pm 2.5\%$ of full scale ), 2.5", 3", 4", 6" ( $\pm 1.5\%$ of full scale )
Operating Temperature Limit	: -20 ~ 200°C ( -4 ~ 400°F )
Application	: general industry, food, petrochemicals, chemicals, fossil fuel, power station, water, air, gas, refrigeration

### SS-A (Direct Mount, Bottom Connection)



### SS-AD (Direct Mount, Center Back Connection)



## P200 SERIES ALL STAINLESS STEEL PRESSURE GAUGE

### SS-B (Surface Mount, Bottom Connection)



### SS-BD (Flush Mount, Center Back Connection)

