

C100 SERIES RIGID TYPE BI-METAL THERMOMETER

Size	: 2.5" (63mm), 3"(75mm), 4"(100mm), 5" (125mm), 6" (150mm)
Measuring Range	: -50 °C up to 600 °C
Dial	: white aluminum with markings and graduations
Window	: glass
Pointer	: black finished aluminum
Construction	: hermetic seal, 304 stainless steel
Stem	: 304 stainless steel, 6mm diameter
Connection	: 1/8", 1/4", 3/8", 1/2"
Sensible Medium	: bi-metallic strip
Mounting	: bottom, back, adjustable angle
Accuracy	: +/- 1 % of full scale
External Reset	: re-cal screw on back of case
Application	: HVAC, drying, water treatment, power generation, food, refrigeration, printing, oven, gas and oil burner, machine tool, chemicals, pulp and paper, petrochemical, pharmaceutical industries, sterilization

* minimum stem length 2.5" on back, bottom, adjustable angle except -10/50°C & 0/60°C 3" stem length on bottom, adjustable angle

C100-AL (Back Connection)



C100 SERIES RIGID TYPE BI-METAL THERMOMETER

C100-AS (Bottom Connection)



C100-BS (Bottom Connection)



C100-BA (Adjustable Angle Connection)

